

SEASON / DROP SS25 / CORE / MAY
BLOCK CORE LS TEE (NEW)
FABRIC STEALTH ANORAK
MANUFACTURER N/A

STATUS
SIZE RANGE
AUTHOR
CREATED - UPDATED

SMS
S - XXL
MEES VISSER
27/02/25 - 00/00/00

LIST OF MEASUREMENTS (CM) (REFER TO 'POINTS OF MEASURE GUIDE')		PROTO 1 REQUEST	PROTO 1			PROTO 2			SALESMAN SAMPLE (SMS)			PRE PRODUCTION (PPS)			PRE SHIPMENT SAMPLE			ACCEPTABLE TOLERANCE	SIZE SPECIFICATIONS & DEVELOPMENT CHART NOTES/COMMENTS	
POM	DESCRIPTION		ACTUAL MEASURE	VARIANCE CM	REQUIRED P2	ACTUAL MEASURE	VARIANCE CM	REQUIRED SMS	ACTUAL MEASURE	VARIANCE CM	REQUIRED PPS	ACTUAL MEASURE	VARIANCE CM	REQUIRED BULK	ACTUAL MEASURE	VARIANCE CM			AUTHOR	NOTES/COMMENTS
			M					M												
A	BACK NECK WIDTH (TOP EDGE RIB TO RIB)		16.5	16.5			0.0	15.0		-15.0			0.0			0.0		0.5		
B	FRONT NECK DROP (FROM TOP EDGE RIB FINISH)		8.3	8.3			0.0	8.0		-8.0			0.0			0.0		0.5		
C	BACK NECK DROP (FROM TOP EDGE RIB FINISH)		1.7	1.7			0.0	1.5		-1.5			0.0			0.0		0.5		
D	½ NECK STRETCH MINIMUM			0.0			0.0	28.0		-28.0			0.0			0.0		0.5		
E	NECK RIB DEPTH		2.3	2.3			0.0	2.5		-2.5			0.0			0.0		0.2		
F	SHOULDER SLOPE FROM HSP (FROM BASE OF RIB)		5.5	5.5			0.0	5.5		-5.5			0.0			0.0		0.5		
G	X-SHOULDER (SEAM TO SEAM)		54.0	54.0			0.0	53.0		-53.0			0.0			0.0		0.5	MV	XL should be: 57
H	X-FRONT @ 18CM FROM HSP		49.0	49.0			0.0	46.0		-46.0			0.0			0.0		0.5		
I	½ ACROSS CHEST @ 2.5 CM UNDER ARMHOLE		59.5	59.5			0.0	58.5		-58.5			0.0			0.0		0.5	MV	XL should be: 66.5
J	½ HEM WIDTH		60.0	60.0			0.0	58.5		-58.5			0.0			0.0		0.5	MV	XL should be: 66.5
K	HEM DEPTH (INCLUDING COVER STITCH)		2.3	2.3			0.0	3.0		-3.0			0.0			0.0		0.5		
L	ARMHOLE STRAIGHT		24.0	24.0			0.0	24.0		-24.0			0.0			0.0		0.5		
M	UNDERARM SLEEVE LENGTH		N/A	#VALUE!			0.0			0.0			0.0			0.0		1.0	MV	match armhole / crown shape of 110001
N	½ BICEP @ 2CM BELOW UNDERARM		25.3	25.3			0.0	23.0		-23.0			0.0			0.0		0.5		
O	½ CUFF WIDTH (SHORT SLEEVE)		21.0	21.0			0.0	19.0		-19.0			0.0			0.0		0.5		
P	CUFF RIB DEPTH		2.3	2.3			0.0	4.5		-4.5			0.0			0.0		0.5		
Q	OVERARM SLEEVE LENGTH FROM SHOULDER (INC. CUFF)		N/A	#VALUE!			0.0	60.5		-60.5			0.0			0.0		0.5	MV	XL should be:
R	FRONT BODY LENGTH FROM HSP (FROM BASE OF NECK RIB)		76.0	76.0			0.0	69.0		-69.0			0.0			0.0		0.5	MV	XL should be: 74.5
S	BACK BODY LENGTH FROM HSP (FROM BASE OF NECK RIB)		76.0	76.0			0.0	69.0		-69.0			0.0			0.0		1.0	MV	XL should be: 74.5
T	FRONT GRAPHIC PLACEMENT(HSP TO GRAPHIC TOP EDGE)		n/a	#VALUE!			0.0			0.0			0.0			0.0		1.0		
U	FRONT GRAPHIC PLACEMENT (CF TO GRAPHIC INSIDE EDGE)		n/a	#VALUE!			0.0			0.0			0.0			0.0		0.5		
				0.0			0.0			0.0			0.0			0.0		0.5		
DATE:								10/3/25												
INITIAL:								MV												
SPECIFICATION NOTES:																				
CF = CENTRE FRONT CB = CENTRE BACK HSP = HIGH SHOULDER POINT SP = SHOULDER POINT																				